



FEATURES

- Stylish and efficient 4 sided traditional lighting fixture for post top mounting
- Lightweight cast aluminum fixture base with stainless steel set screws for installation
- Slip fits over common 2 7/8" and 3" OD tenons on most decorative poles
- Durable Powder Coat Finish
- 0-10v Dimming Capability
- ETL Listed

LED LIGHT SOURCE OPTIONS

- 3 Power Levels
 - 3 Color Temperatures
 - 4 Light Distributions
- (HID Version Available-Consult Factory)

MATERIALS

- Base, Cage, Hat, Finial - Cast Aluminum (A356)
- Hardware - Stainless Steel
- Lenses - Acrylic

LENS OPTION

- **NL** - No Lens (Highest LPW)
- **CA** - Clear Acrylic
- **TA** - Textured Acrylic
- **PA** - Prismatic Acrylic
- **FA** - Frosted Acrylic
- **WA** - White Acrylic

ACCESSORIES

- **PCLL** - PCL for LED Fixtures
- **26HSS** - 180° House Side Shield
- **SP1** - 10kV/10kA Surge Protection

LED LIGHT SOURCE CONFIGURATIONS

- G2LED40**—1 Driver, 1 LED Module, 1 Optic
- G2LED65**—1 Driver, 1 LED Module, 1 Optic
- G2LED80**—1 Driver, 2 LED Modules, 2 Optics

DRIVER

- 0-10v Dimming Compatible
- 120 to 277 Auto Sensing
- Class 2, Class P
- Minimum Rating IP66

LED MODULE

- 12 High efficacy multi-die packages
- 2x6 LED Configuration
- 80CRI—2700, 3000, 4000 CCT

LED OPTICS

- 2x6 Multi Lens
- PMMA (Acrylic)
- IES Type II, III, IV, V
- Silicone Gasket
- IP66 System



Finish

The fixture will be finished with an electrostatically applied polyester powder coat suitable for exterior use. The fixtures are pretreated using industry standard environmentally responsible processes for a long lasting and durable finish.

Standard Finishes

- BK** - Black (Gloss)
- BT** - Black (Textured)
- SB** - Statuary Bronze
- GN** - Green

Premium Finishes

- WH** - White (Gloss)
- CV** - Copper Vein
- GV** - Green Vein
- CF** - Custom Finishes

LED Light Source Performance Data
In GT1413-CA Fixture

GT1413-CA			2700K (27K)		3000K (30K)		4000K (40K)	
MODULE NAME	NOM WATT	LIGHT DISTRIBUTION	DELIVERED LUMENS	EFFICACY (LPW)	DELIVERED LUMENS	EFFICACY (LPW)	DELIVERED LUMENS	EFFICACY (LPW)
G2LED40	41.2	T2	3774	91.6	4048	98.3	4220	102.4
		T3	3750	91.0	4023	97.6	4193	101.8
		T4	3702	89.9	3971	96.4	4140	100.5
		T5	3808	92.4	4085	99.2	4258	103.4
G2LED65	67.9	T2	5420	79.8	5815	85.6	6061	89.3
		T3	5387	79.3	5779	85.1	6024	88.7
		T4	5318	78.3	5705	84.0	5947	87.6
		T5	5470	80.6	5868	86.4	6117	90.1
G2LED80	82.2	T2	7163	87.1	7684	93.5	8010	97.4
		T3	7115	86.6	7633	92.9	7956	96.8
		T4	7025	85.5	7536	91.7	7855	95.6
		T5	7614	92.6	8168	99.4	8514	103.6

LED Light Source Options

Light Source	Nominal Power	Distribution	CCT
G2LED40	41.2 W	Type II (T2) Type III (T3)	2700K (27K)
G2LED65	67.9 W	Type IV (T4)	3000K (30K)
G2LED80	82.2 W	Type V (T5)	4000K (40K)

LED Drivers are auto voltage sensing, standard 120V through 277V (347, 480V Version Available-Consult Factory)

Ordering Guide

	Luminaire	Lens Material	LED Light Source	Distribution Type	CCT	Optional Photocell	Optional House Side Shield	Finish
EXAMPLE	GT1413	NL	G2LED80	T3	40K	PCLL	26HSS	BT
	GT1413	NL	G2LED40	T2	27K	PCLL	26HSS	BK
		CA	G2LED65	T3	30K			BT
		TA	G2LED80	T4	40K			SB
		PA		T5				GN
		FA						Premium Finishes
		WA						WH, CV, GV, CF
	Required					Optional		Choose Finish