



**FEATURES**

- Stylish and efficient 6 sided traditional lighting fixture for post top mounting
- Lightweight cast aluminum fixture base with stainless steel set screws for installation
- Slip fits over common 2 7/8" and 3" OD tenons on most decorative poles
- Durable Powder Coat Finish
- 0-10v Dimming Capability
- ETL Listed

**LED LIGHT SOURCE OPTIONS**

- 2 Power Level
  - 3 Color Temperatures
  - 4 Light Distributions
- (CFL & Incandescent Version Available-Consult Factory)

**MATERIALS**

- Base, Cage, Hat, Finial - Cast Aluminum (A356)
- Hardware - Stainless Steel
- Lenses - Acrylic

**LENS OPTION**

- **NL** - No Lens (Highest LPW)
- **CA** - Clear Acrylic
- **TA** - Textured Acrylic
- **PA** - Prismatic Acrylic
- **FA** - Frosted Acrylic
- **WA** - White Acrylic

**ACCESSORIES**

- **PCLL** - PCL for LED Fixtures
- **26HSS** - 180° House Side Shield
- **SP1** - 10kV/10kA Surge Protection

**LED LIGHT SOURCE CONFIGURATIONS**

**G2LED26**—1 Driver, 1 LED Module, 1 Optic

**G2LED40**—1 Driver, 1 LED Module, 1 Optic

**DRIVER**

0-10v Dimming Compatible  
120 to 277 Auto Sensing  
Class 2, Class P  
Minimum Rating IP66

**LED MODULE**

12 High efficacy multi-die packages  
2x6 LED Configuration  
80CRI—2700, 3000, 4000 CCT

**LED OPTICS**

2x6 Multi Lens  
PMMA (Acrylic)  
IES Type II, III, IV, V  
Silicone Gasket  
IP66 System



**Finish**

The fixture will be finished with an electrostatically applied polyester powder coat suitable for exterior use. The fixtures are pretreated using industry standard environmentally responsible processes for a long lasting and durable finish.

Standard Finishes

- BK** - Black (Gloss)
- BT** - Black (Textured)
- SB** - Statuary Bronze
- GN** - Green

Premium Finishes

- WH** - White (Gloss)
- CV** - Copper Vein
- GV** - Green Vein
- CF** - Custom Finishes

LED Light Source Performance Data  
For Fixture with CA LENS

GT1611-CA			2700K (27K)	3000K (30K)	4000K (40K)
MODULE NAME	NOM WATT	LIGHT DISTRIBUTION	DELIVERED EFFICACY LUMENS (LPW)	DELIVERED EFFICACY LUMENS (LPW)	DELIVERED EFFICACY LUMENS (LPW)
G2LED26	26	T2	-	-	-
		T3	-	-	-
		T4	-	-	-
		T5	-	-	-
G2LED40	41	T2	-	-	-
		T3	-	-	-
		T4	-	-	-
		T5	-	-	-

LED Light Source Options

Light Source	Nominal Power	Distribution	CCT
G2LED26	26 W	Type II (T2) Type III (T3)	2700K (27K)
G2LED40	41 W	Type IV (T4)	3000K (30K)
		Type V (T5)	4000K (40K)

LED Drivers are auto voltage sensing, standard 120V through 277V (347, 480V Version Available-Consult Factory)

**Ordering Guide**

Luminaire	Lens Material	LED Light Source	Distribution Type	CCT	Optional Photocell	Optional House Side Shield	Finish
EXAMPLE GT1611	- NL	/ G2LED40	- T3	- 40K	/ PCLL	/ 26HSS	/ BT
GT1611	NL	G2LED40	T2	27K	PCLL	26HSS	BK
	CA		T3	30K			BT
	TA		T4	40K			SB
	PA		T5				GN
	FA						Premium Finishes
	WA						WH, CV, GV, CF
Required					Optional		Choose Finish